

Why use flexible pipe fittings?

Superior and long-lasting resistance to leaks.

Flexible pipe fittings are designed to provide leak-proof seals for DWV (drain, waste & vent) pipe. Because of their ability to flex without rupturing, these products ensure a tight, long-lasting leak-proof seal even in cases of pipe separation or deflection. The flexible PVC and neoprene material used in the manufacture of these products is resistant to most acids encountered in normal usage and therefore offer superior resistance to corrosion. Flexible pipe fittings are also designed to work with a variety of common pipe materials, including plastic, cast iron, clay, copper, concrete, steel and asbestos.

Ease of installation.

In addition, flexible pipe fittings feature greatly simplified installation. Each fitting includes one or two series 300 stainless steel clamps designed to work at 60 inch-pounds of pressure to ensure a tight seal. There is no need for gluing, soldering or welding. To further simplify installation, use our flexible pipe fitting torque wrench (sold separately) which is specifically designed to release once the optimum pressure of 60 inch-pounds has been achieved.

Flexible Couplings

Flexible pipe couplings are designed to replace standard DWV fittings. Suitable for use on cast iron, plastic, copper or steel. Can be used to join pipe sections of dissimilar materials. Also suitable for use underground. Made of flexible PVC.



Meets: ASTM C-1173, C-1277, C1460, CISPI 310, IAPMO PS 109, PS90, & CSA B602

SKU	SIZE	PRESSURE RATING	TEMP RATING *	SP	FP	UPC
4374559	1-1/2" x 1-1/4"	4.3 PSI	140F	40	40	0 45734 62354 5
4388062	1-1/2" x 1-1/2"	4.3 PSI	140F	40	40	0 45734 62355 2
4407946	2" x 1-1/2"	4.3 PSI	140F	40	40	0 45734 62356 9
4411138	2" x 2"	4.3 PSI	140F	40	40	0 45734 62357 6
4449815	3" x 1-1/2"	4.3 PSI	140F	10	10	0 45734 62358 3
4489324	3" x 2"	4.3 PSI	140F	20	20	0 45734 62359 0
4539557	3" x 3"	4.3 PSI	140F	40	40	0 45734 62360 6
4547162	4" x 3"	4.3 PSI	140F	40	40	0 45734 62361 3
4560280	4" x 4"	4.3 PSI	140F	40	40	0 45734 62362 0
4570768	6" x 4"	4.3 PSI	140F	10	10	0 45734 62363 7
4583241	6" x 6"	4.3 PSI	140F	10	10	0 45734 62364 4

* Non-consistent

Clay/Concrete Pipe Couplings

For connecting pipes of various specialty materials including clay and concrete to materials including cast iron and asbestos. Suitable for use underground. Made of flexible PVC.



Meets: ASTM C-1173, C-1277, C1460, CISPI 310, IAPMO PS 109, PS90, & CSA B602

SKU	SIZE	PRESSURE RATING	TEMP RATING *	SP	FP	UPC
Clay to Cast Iron						
5184213	4" x 3"	4.3 PSI	140F	20	20	0 45734 62431 3
5040746	4" x 4"	4.3 PSI	140F	30	30	0 45734 62424 5
Clay to Asbestos Cement Fibre or Ductile Iron Pipes						
5345764	4" x 4"	4.3 PSI	140F	20	20	0 45734 62440 5
Clay to Clay						
5347695	3" x 3"	4.3 PSI	140F	20	20	0 45734 62441 2
Clay to Cast Iron						
5370135	4" x 4"	4.3 PSI	140F	20	240	0 45734 62444 3

* Non-consistent

No-Hub Couplings

Connects no-hub drain pipes of similar material. Can be used on cast iron, plastic and steel drain pipes. Suitable for use underground. Neoprene gasket.



SKU	SIZE	PRESSURE RATING	TEMP RATING *	SP	FP	UPC
9822297	1-1/2"	4.3 PSI	140F	30	30	0 45734 62534 1
5369186	2" x 1-1/2"	4.3 PSI	140F	30	30	0 45734 62443 6
4590774	2"	4.3 PSI	140F	100	100	0 45734 62365 1
4597860	2" x 2"	4.3 PSI	140F	100	100	0 45734 62366 8
4607248	3"	4.3 PSI	140F	100	100	0 45734 62367 5

* Non-consistent



Meets: ASTM C-1173, C-1277, C1460, CISPI 310, IAPMO PS 109, PS90, & CSA B602

Shielded No-Hub Couplings

Connects no-hub drain pipes of dissimilar materials. Can be used on any combination of plastic, steel or extra-heavy cast iron pipes. Series 300 stainless steel shield and neoprene gasket. Not recommended for use underground.



SKU	SIZE	PRESSURE RATING	TEMP RATING *	SP	FP	UPC
5190186	1-1/2"	4.3 PSI	140F	24	24	0 45734 62432 0
5122064	2"	4.3 PSI	140F	24	24	0 45734 62428 3
5236567	3"	4.3 PSI	140F	24	24	0 45734 62433 7
5138748	4"	4.3 PSI	140F	24	24	0 45734 62429 0

* Non-consistent



Meets: ASTM C-1173, C-1277, C1460, CISPI 310, IAPMO PS 109, PS90, & CSA B602

Corrugated Pipe Couplings

For specific use underground. Designed with ring stopper on the inside of the coupling to connect corrugated polyethylene drainage pipe and irrigation systems to plastic DWV pipe. Made of flexible PVC.



SKU	SIZE	PRESSURE RATING	TEMP RATING *	SP	FP	UPC
5063623	4" x 4"	4.3 PSI	140F	20	20	0 45734 62426 9

* Non-consistent



Meets: ASTM C-1173, C-1277, C1460, CISPI 310, IAPMO PS 109, PS90, & CSA B602

Socket Couplings

For socket to pipe or pipe to pipe connections. Allows for the repair of plastic pipes without replacing good fittings. Can also be used with plastic traps. Suitable for use underground. Made of flexible PVC.



Meets: ASTM C-1173, C-1277, C1460, CISPI 310, IAPMO PS 109, PS90, & CSA B602

SKU	SIZE	PRESSURE RATING	TEMP RATING *	SP	FP	UPC
Socket to Pipe						
5323134	1-1/2"	4.3 PSI	140F	20	20	0 45734 62438 2
5303326	2"	4.3 PSI	140F	20	20	0 45734 62437 5
5295613	3"	4.3 PSI	140F	20	20	0 45734 62436 8
5261953	4"	4.3 PSI	140F	20	20	0 45734 62435 1
Socket to Socket						
5331848	1-1/2"	4.3 PSI	140F	20	20	0 45734 62439 9
5352679	2"	4.3 PSI	140F	20	20	0 45734 62442 9
5237383	3"	4.3 PSI	140F	20	20	0 45734 62434 4
5178363	4"	4.3 PSI	140F	20	20	0 45734 62430 6

* Non-consistent

Flexible Tees & Elbows

Connects cast iron, copper, plastic or steel pipe. Extra long for greater versatility. Good for replacing fittings that have been cut off at the joint. For above ground use only. Made of flexible PVC.



Meets: ASTM C-1173, C-1277, C1460, CISPI 310, IAPMO PS 109, PS90, & CSA B602

SKU	SIZE	PRESSURE RATING	TEMP RATING *	SP	FP	UPC
Elbows						
4731139	1-1/2" x 1-1/2"	4.3 PSI	140F	20	20	0 45734 62376 7
4746160	2" x 2"	4.3 PSI	140F	20	20	0 45734 62377 4
4746319	3" x 3"	4.3 PSI	140F	10	10	0 45734 62378 1
4755666	4" x 4"	4.3 PSI	140F	5	5	0 45734 62379 8
Tees						
4714424	1-1/2" x 1-1/2" x 1-1/2"	4.3 PSI	140F	20	20	0 45734 62372 9
4720272	2" x 2" x 2"	4.3 PSI	140F	20	20	0 45734 62373 6
4721924	3" x 3" x 3"	4.3 PSI	140F	10	10	0 45734 62374 3
4729646	4" x 4" x 4"	4.3 PSI	140F	5	5	0 45734 62375 0

* Non-consistent

Flexible Pipe Caps

For capping pipe ends. Convex face allows the cap to withstand greater pressure for testing purposes and minimizes ballooning. For temporary or permanent use. Can be used with any material. Suitable for underground use. Made of flexible PVC.



Meets: ASTM C-1173, C-1277, C1460, CISPI 310, IAPMO PS 109, PS90, & CSA B602

SKU	SIZE	SP	FP	UPC
4613386	1-1/2"	40	40	0 45734 62368 2
4643128	2"	40	40	0 45734 62369 9
4679528	3"	40	40	0 45734 62370 5
4703658	4"	40	40	0 45734 62371 2

* FLEXIBLE PIPE FITTINGS ARE NOT FOR USE IN PRESSURIZED PLUMBING SYSTEMS *

Pipe Hub Donuts

For the compression sealing of sewer pipe joints and DWV connections such as sockets, bells, hubs and spigots.



Meets: ASTM C-1173, C-1277, C1460, CISPI 310, IAPMO PS 109, PS90, & CSA B602

SKU	SIZE	SP	FP	UPC
4755765	2" x 1-1/2"	20	20	0 45734 62380 4
4776407	2" x 2"	20	20	0 45734 62408 5
4788691	3" x 1-1/2"	20	20	0 45734 62409 2
4821609	3" x 2"	20	20	0 45734 62410 8
4842324	3" x 3"	20	20	0 45734 62411 5
4897559	4" x 1-1/2"	20	20	0 45734 62412 2
4914412	4" x 2"	20	20	0 45734 62413 9
4919569	4" x 3"	20	20	0 45734 62414 6
4932604	4" x 4"	20	20	0 45734 62415 3

Drain Pipe Connections

Standard: Ideal for extending, altering or repairing drain pipes. Can be used for installation of condensate lines on air conditioners. **Not for use in potable water applications**
Tubular: Quick and easy way to extend, alter or repair any combination of 1-1/2" or 1-1/4" brass or plastic drain pipes. For above ground use only. Made of flexible PVC.



SKU	SIZE	SP	FP	UPC
For Plastic, Cast Iron, Steel or Copper				
5096524	3/4"	20	20	0 45734 62427 6
5051115	1"	20	20	0 45734 62425 2
Tubular - For Brass or Plastic				
4981718	1-1/2" or 1-1/4"	20	200	0 45734 62418 4

Drain & Trap Connections

Connects tubular traps to all common 1-1/4" or 1-1/2" plastic, steel, cast iron or copper drain pipes. For above ground use only. Made of flexible PVC.



SKU	SIZE	SP	FP	UPC
4990305	1-1/4" or 1-1/2"	20	200	0 45734 62419 1
5003496	2"	20	200	0 45734 62420 7

Dishwasher Drain Connections

Connects dishwasher drain hose to sink drain or to a garbage disposal. Made of flexible PVC.



SKU	SIZE	SP	FP	UPC
4956678	N/A	20	240	0 45734 62416 0

Flexible Drain Trap

Replaces any 1-1/4" or 1-1/2" metal or plastic J-bend trap. For above ground use only. Made of flexible PVC.



SKU	SIZE	SP	FP	UPC
4960563	1-1/4" or 1-1/2"	20	80	0 45734 62417 7

Washing Machine Drain Hose Gripper

Ensure a secure connection between clothes washer drain hoses and the standpipes. Fits both 2" and 1-1/2" standpipes and most washing machine hoses 1" -1-7/16" diameter. Made of flexible PVC.



SKU	SIZE	SP	FP	UPC
5010699	N/A	20	200	0 45734 62421 4

Flange Repair Kit

For the repair of broken toilet flanges. Prevents toilet from shifting or leaking. Works with plastic, brass, cast iron or copper flanges.



SKU	SIZE	SP	FP	UPC
5011176	N/A	20	240	0 45734 62422 1

Torque Wrench

Tightens steel bands to 60 inch-pounds of torque. Automatically releases once correct torque has been achieved.



SKU	SIZE	SP	FP	UPC
5019864	N/A	25	100	0 45734 62423 8

* FLEXIBLE PIPE FITTINGS ARE NOT FOR USE IN PRESSURIZED PLUMBING SYSTEMS *